

Type 27 Cotton Fiber Grinding & Blending Wheels

PRODUCT FEATURES

- Grind and finish in one step
- Smooth controlled grinding action
- Non-loading on aluminum
- Superior surface finishes on stainless steel and aluminum
- Long life and durability

SPECIFICATIONS

Grain sizes: A24, A36, A54, A80, A120. Silicon carbide available.

Bonds: MTX - Tough Resin Bond for grinding

GFX - Synthetic Latex Bond for blending and finishing

GFX Bond

Use this bond for blending and finishing applications on stainless steel and aluminum. It resists loading and is resilient for smooth operation on stainless steel tanks, vessels, and other fabrications.

A36 GFX: Blending on stainless steel and aluminum

MTX Bond

Use this bond for light or medium weld removal. Its resilient resin bond provides better control of cut rate. It resists loading on aluminum and offers excellent results on all non-ferrous materials.

A24 MTX: Grinding aluminum

Availability

Diameter	Thickness	Arbor Holes	Max RPM
4	1/8, 3/16, 1/4	3/8, 5/8	15,300
4-1/2	1/8, 3/16, 1/4	7/8	13,300
5	3/16, 1/4	7/8	12,200
7	3/16*	7/8	8,500
7	1/4	7/8	8,500
9	3/16*	7/8	6,600
9	1/4	7/8	6,600

Available with 5/8 - 11 throw away adapters, reusable adapter kits also available.



Angle Grinder



800.225.8182
www.rexcut.com
info@rexcut.com

youtube.com/user/rexcutabrasives
twitter.com/rexcut
linkedin.com/company/rexcut
facebook.com/rexcut

an employee owned company



Improve Your Daily Grind