

# Rex-Cut Abrasives Cut-Off Wheel Line

Each cut-off wheel in the Rex-Cut line is designed to cut extremely fast and cool. These premium wheels are constructed with a fiberglass reinforced resinoid bond for free cutting action. Rex-Cut cut-off wheels feature a thin profile for minimal kerf loss and are *Made in the USA*.

## VERSA-CUT

General purpose cut-off wheel manufactured with premium Aluminum Oxide grain for optimum performance.

### Metals

All grades of steel including: carbon steel, mild steel, and cold rolled steel

### Applications

Cutting tube, pipe, rails, rebar, and sheet metal  
Trimming castings



## ALPHA-GREEN

Engineered with an INOX formula specialized for stainless steel cutting.

### Metals

Stainless Steel and Nickel Alloys

### Applications

Cutting tube, pipe, rails and sheet metal  
Trimming castings



## ALUMINATOR

Specially formulated to prevent loading.

### Metals

Aluminum, Brass, and other non-ferrous metals

### Applications

Cutting tube, pipe, rails and sheet metal  
Trimming castings



800.225.8182  
www.rexcut.com  
info@rexcut.com



youtube.com/user/rexcutabrasives  
twitter.com/rexcut  
linkedin.com/company/rexcut  
facebook.com/rexcut

*an employee owned company*



Improve Your Daily Grind

## VERSA-CUT

### Type 1

Diameter x Thickness x Arbor		Specification	Max RPM	Part No.	Box Qty.
inch	mm				
4.5 x .045 x 7/8	115 x 1.1 x 22.2	A46-BF	13,300	800201	50
6 x .045 x 7/8	152 x 1.1 x 22.2	A46-BF	10,200	800203	25

### Type 27

Diameter x Thickness x Arbor		Specification	Max RPM	Part No.	Box Qty.
inch	mm				
4.5 x .045 x 7/8	115 x 1.1 x 22.2	A46-BF	13,300	800300	50
6 x .045 x 7/8	152 x 1.1 x 22.2	A46-BF	10,200	800302	25



## ALPHA-GREEN

### Type 1

Diameter x Thickness x Arbor		Specification	Max RPM	Part No.	Box Qty.
inch	mm				
3 x .040 x 1/4	75 x 1 x 6	A60-INOX-BF	25,100	860010	50
3 x .045 x 1/4	75 x 1.1 x 6	A46-INOX-BF	25,100	860011	50
3 x .040 x 3/8	75 x 1 x 10	A60-INOX-BF	25,100	860000	50
3 x .045 x 3/8	75 x 1.1 x 10	A46-INOX-BF	25,100	860001	50
4 x .040 x 3/8	100 x 1 x 10	A60-INOX-BF	15,000	860012	50
4 x .045 x 3/8	100 x 1.1 x 10	A46-INOX-BF	15,000	860013	50
4 x .040 x 5/8	100 x 1 x 16	A60-INOX-BF	15,000	860002	50
4 x .045 x 5/8	100 x 1.1 x 16	A46-INOX-BF	15,000	860003	50
4.5 x .040 x 7/8	115 x 1 x 22.2	A60-INOX-BF	13,300	860004	50
4.5 x .045 x 7/8	115 x 1.1 x 22.2	A46-INOX-BF	13,300	860005	50
5 x .040 x 7/8	125 x 1 x 22.2	A60-INOX-BF	12,200	860006	50
6 x .040 x 7/8	152 x 1 x 22.2	A60-INOX-BF	10,200	860008	25
6 x .045 x 7/8	152 x 1.1 x 22.2	A46-INOX-BF	10,200	860009	25



### Type 27

Diameter x Thickness x Arbor		Specification	Max RPM	Part No.	Box Qty.
inch	mm				
4 x .040 x 5/8	100 x 1 x 16	A60-INOX-BF	15,000	870002	50
4 x .045 x 5/8	100 x 1.1 x 16	A46-INOX-BF	15,000	870003	50
4.5 x .040 x 7/8	115 x 1 x 22.2	A60-INOX-BF	13,300	870004	50
4.5 x .045 x 7/8	115 x 1.1 x 22.2	A46-INOX-BF	13,300	870005	50
5 x .040 x 7/8	125 x 1 x 22.2	A60-INOX-BF	12,200	870006	50
6 x .040 x 7/8	152 x 1 x 22.2	A60-INOX-BF	10,200	870008	25
7 x 1/16 x 7/8	178 x 1.6 x 22.2	A46-INOX-BF	8,600	870010	25

## ALUMINATOR

### Type 1

Diameter x Thickness x Arbor		Specification	Max RPM	Part No.	Box Qty.
inch	mm				
4 x .045 x 5/8	100 x 1.1 x 16	AL46	15,000	800200	25
4.5 x .045 x 7/8	115 x 1.1 x 22.2	AL46	13,300	800201	25
5 x .045 x 7/8	125 x 1.1 x 22.2	AL46	12,200	800202	25
6 x .045 x 7/8	152 x 1.1 x 22.2	AL46	10,200	800203	25

### Type 27

Diameter x Thickness x Arbor		Specification	Max RPM	Part No.	Box Qty.
inch	mm				
4.5 x .045 x 7/8	115 x 1.1 x 22.2	AL46	13,300	800300	25
5 x .045 x 7/8	125 x 1.1 x 22.2	AL46	12,200	800301	25
6 x .045 x 7/8	152 x 1.1 x 22.2	AL46	10,200	800302	25
7 x 1/16 x 7/8	178 x 1.6 x 22.2	AL46	8,600	800303	25

